

QUADRO

HORIZONTAL LIFELINE

TECHNICAL DATA SHEET



The Quadro is a temporary horizontal lifeline system designed to be used for restraint or fall arrest applications. Spanning up to 25m / 82ft the system can accommodate up to 4 users with a maximum user weight of 100kg / 220lb each.



Rope Vice Tensioner

The rope is tensioned by simply depressing and rotating the built-in handle. Tension can be safely removed by pulling the release arm.



Swivel Eye

Lightweight captive swivel eye prevents the rope from twisting during use.



Sewn Terminations

Stitched with contrasting thread for easy visual inspection.

NOTE: System length is measured between the bearing points of the anchor points, if using anchor straps ensure they do not extend the length of the system greater than 25m / 82ft.



Double Braid

16mm / 5/8" rope offers strength and durability by utilising an outer sheath to protect the inner core.

QUADRO

HORIZONTAL LIFELINE

TECHNICAL DATA SHEET

SKU	Description	Span	Weight
30803	Quadro Horizontal Lifeline with Rope Vice Tensioner, Drawstring Rope Bag, 25m Double Braided Rope, 4 x Aluminium O-rings, 2 x Steel Karabiners, 2 x Cross Arm Straps	25m / 82ft	8.2kg / 1.8lb



Features

- Inline swivel prevents rope from twisting
- Aluminium O-rings
- Steel karabiners
- Contrast colour stitching for easy inspection
- **Maximum Length**
25m / 82ft
- **Maximum Number of Users**
4 in restraint or fall arrest with a maximum user weight of 100kg / 220lb each



Standards

- EN 795 Class C
- EN 795 Class B (anchor straps)